






SCX-5115/SCX-5315F	SCX-6220/SCX-6320F	SF-560 Fax, Copy	SF-565P Fax, Copy, Print, Scan	SF-755P Fax, Copy, Print, Scan
 <p>This 4-in-1 multifunction digital copier, fax (5315F), printer and color scanner is a convenient space-saving unit.</p>	 <p>Duplex print, scan and copy plus fax (6320F) and optional network printing and scanning for busy workgroups.</p>	 <p>A fast plain paper laser fax and copy solution for busy office environments.</p>	 <p>Compact, feature-packed 4-in-1 machine for maximum space savings in small office environments.</p>	 <p>A high-capacity, high-speed, full-function 4-in-1 MFP ideal for even the busiest medium-sized offices.</p>
Best for businesses	Best for businesses	Best for businesses	Best for small offices	Best for businesses
Yes Yes SCX-5315F only Yes	Yes Yes SCX-6320F only Yes	No Yes Yes No	Yes Yes Yes Yes	Yes Yes Yes Yes
Up to 16 ppm Less than 13 seconds Up to 1200 dpi effective output 8 MB RAM PCL 6 Up to 18,750 pages per month	Up to 22 ppm Less than 9 seconds Up to 1200 dpi effective output 6220: 32 MB RAM (64 MB max.), 6320F: 48 MB RAM (80 MB max.) PCL 6, Postscript Level 3 optional Up to 20,000 pages per month	N/A N/A N/A N/A Up to 10,000 pages per month	Up to 17 ppm Less than 12 seconds Up to 600 dpi effective output 4 MB SPL (host-based printing) Up to 10,000 pages per month	Up to 17 ppm Less than 12 seconds Up to 600 dpi effective output 4 MB SPL (host-based printing) Up to 10,000 pages per month
Up to 15 cpm Less than 10 seconds Up to 600 dpi/1200 dpi effective output 25 – 400% 999 pages	Up to 22 cpm Less than 8 seconds Up to 600 dpi/600 dpi effective output 25-400% 999 pages	Up to 17 cpm Less than 30 seconds Up to 300 dpi effective output/N/A 50 – 150% 99 pages	Up to 17 cpm Less than 30 seconds Up to 300 dpi/300 dpi effective output 50-200% 99 pages	Up to 17 cpm Less than 20 seconds Up to 600 dpi/600 dpi effective output 50-200% 99 pages
Fax Specs For SCX-5315F Only 33.6 Kbps Approx. 3 sec. per page ITU-T Group 3, ECM MH/MR/MMR, JPEG 4 MB (up to 320 pages) Up to 400 dpi (200 dpi color) 40 one-touch dial, 80 speed dial 72 hours	Fax Specs For SCX-6320F Only 33.6 Kbps Approx. 3 sec. per page ITU-T Group 3, ECM MH/MR/MMR, JPEG/JBIG 16 MB (up to 1,280 pages) Up to 400 dpi (200 dpi color) 20 one-touch dial, 80 speed dial 100 hours	33.6 Kbps Approx. 3 sec. per page ITU-T Group 3 MH/MR/MMR 2 MB (up to 160 pages) Up to 203 x 392 dpi 20 one-touch dial, 80 speed dial 96 hours	33.6 Kbps Approx. 3 sec. per page ITU-T Group 3, ECM MH/MR/MMR 2 MB (up to 160 pages) Up to 203 x 392 dpi 20 one-touch dial, 80 speed dial 96 hours	33.6 Kbps Approx. 2.5 sec. per page ITU-T Group 3, ECM MH/MR/MMR, JBIG 5 MB (up to 400 pages) Up to 300 x 300 dpi 40 one-touch dial, 150 speed dial 72 hours
Up to 600 dpi/4800 dpi Color CCD 1 bit, 8 bit, 24 bit (32 bit internal) A4/letter	Up to 600 dpi/4800 dpi Color CCD 1 bit, 8 bit, 24 bit (32 bit internal) A4/letter	N/A N/A N/A N/A	Up to 200 dpi/1200 dpi CIS, Mono 1 bit, 8 bit, N/A 8.2" x 15.7"	Up to 600 dpi/4800 dpi Color CIS 1 bit, 8 bit, 24 bit (32 bit internal) 8.2" x 15.7"
8.5" x 14" legal 550-sheet cassette, 100-sheet multipurpose tray 250 sheets 30 sheets	8.5" x 14" legal 550-sheet cassette, 100-sheet multipurpose tray 250 sheets 50 sheets	8.5" x 14" legal 250-sheet cassette, 1-sheet manual tray 150 sheets 20 sheets	8.5" x 14" legal 250-sheet cassette, 1-sheet manual tray 150 sheets 20 sheets	8.5" x 14" legal 250-sheet cassette, 1-sheet manual tray (250-sheet cassette optional) 150 sheets 50 sheets
SCX-5312D6, SCX-5315R2 Toner: 6,000 pages, Drum: 15,000 pages	SCX-6320D8, SCX-6320R2 Toner: 8,000 pages (Drum: 20,000 pages)	SCX-4216D3 3,000 pages, 1,000 pages	SCX-4216D3 3,000 pages, 1,000 pages	SCX-4216D3 3,000 pages
USB 1.1 (compatible with USB 2.0), IEEE-1284 parallel 10/100 Base-TX Ethernet, 802.11b wireless Windows 98, Me, 2000, XP, Various Linux systems (via USB only) 16 MB RAM Less than 50 dBA 35 watts, 90 watts, 350 watts 21" x 17" x 18" 55 lbs.	USB 2.0, IEEE-1284 parallel 10/100 Base-TX Ethernet, 802.11b wireless Windows 95, 98, Me, NT 4.0, 2000, XP, Various Linux systems (via USB only) 32 MB RAM, 48 MB RAM Less than 60 dBA 35 watts, 115 watts, 430 watts 21.3" x 17.4" x 19.2" 55 lbs.	USB 1.1 (compatible with USB 2.0), IEEE-1284 parallel N/A Windows 95, 98, Me, NT 4.0, 2000, XP, Various Linux systems (via USB only) 8 MB RAM Less than 52 dBA 12 watts, 85 watts, 300 watts 17" x 16.6" x 13.7" 21.4 lbs.	USB 1.1 (compatible with USB 2.0), IEEE-1284 parallel N/A Windows 98, Me, 2000, XP, Various Linux systems (via USB only) 8 MB RAM Less than 52 dBA 10 watts, 95 watts, 300 watts 17" x 16.6" x 13.7" 21.4 lbs.	USB 2.0, IEEE-1284 parallel N/A Windows 98, Me, 2000, XP, Various Linux systems (via USB only) 32 MB RAM Less than 52 dBA 10 watts, 85 watts, 300 watts 15.1" x 16.4" x 13.2" 24.2 lbs.